


Media: air – water – light oil - steam
 Pressure range: 0 - 4.9 or 0.5 - 20 Bar
 Media temperature: +200°C Max
 Ambient temperature: -20°C to +60°C
 Media viscosity: 50 centistokes max
 Mounting: coil upright
 Opening / Closing 200 mSec Max



LATCHING

2/2 Brass

1/8 - 2

LATCHING

2 WAY DIRECT + SERVO ASSIST

0 – 20 Bar

TYPE LSA



PRESSURE

Ø Port BSP	Ø Orifice (mm)	Flow Kv Ltr/ min	Coil	Pressure Rating (Bar) Max ΔP			Part Number
				Min	Steam	Air/ Water	
1/8	3	5.2	WPG1	0		4.9	LSA6A + voltage
1/4	3	5.2	WPG1	0		4.9	LSA8A + voltage
3/8	4	9.7	WPG2	0		4.9	LSA10A + voltage
3/8	15	75	WPG2	0.5	12	20	LSA14 + voltage
1/2	15	75	WPG2	0.5	12	20	LSA15 + voltage
3/4	20	155	WPG2	0.5	12	20	LSA20 + voltage
1	25	220	WPG2	0.5	12	20	LSA25 + voltage
1 1/4	35	433	WPG2	0.5	12	20	LSA35 + voltage
1 1/2	35	433	WPG2	0.5	12	20	LSA40 + voltage
2	50	800	WPG2	0.5	12	20	LSA50 + voltage

OPTIONS

IP67 UL + CSA Approved Coil & IP65 PG11 LED Connector DIN43650A
 NPT Thread
 Stainless Steel Body, High Pressure, Flanged and other custom made options available upon request

ELECTRICAL DATA

Voltage (-10% + 10%) Continuous duty 100%		Coil	Power Consumption	Insulation class	Enclosure	Electrical connections
=	12 – 24 (DC)	WPG1	12 Watts	H 180°C	IP 65 With Connector	3 spades DIN 43650 DIN 40050 VDE0110
		WPG2	18 Watts			

CONSTRUCTION

Body: Brass
 Tube and Spring: 304 Stainless Armature: 430F Stainless Other internal parts: Stainless No Shading Ring
 Seals and gaskets: PTFE
 Moulded coil: Resin

REPAIR KIT

Coil	Coil size (WPG1 or WPG2) + voltage (DC Only)
Piston	SP + valve part number - PISTON
Armature assembly	SP + valve part number - ARMATURE

OVERALL DIMENSIONS

Model	A	B	C	D	E	F	G	H	Kg
LSA6	41	19	86	41	40	-	1/8	10.5	0.47
LSA8	41	19	86	41	40	-	1/4	10.5	0.43
LSA10	50	25	91	52	45	-	3/8	11.7	0.56
LSA14	67	48	123	67	52	42	3/8	15	1.13
LSA15	67	48	123	67	52	42	1/2	15	1.1
LSA20	96	72	149	67	52	42	3/4	25	1.53
LSA25	96	72	149	67	52	42	1	25	1.85
LSA35	120	90	168	52	45	41	1 1/4	33	3.3
LSA40	120	90	168	52	45	41	1 1/2	33	3.25
LSA50	150	122	203	52	45	41	2	40.5	6.8

