



Wednesday, 09 April 2025

We hereby declare that the products specified below meet the basic health and safety requirements.

Product description:

Connexion ASPV Pneumatic Angle seat piston valve.

Sizes DN10 to DN100

Pressure: PN16 (16 Bar)

Material: 304 and 316 Stainless steel

Temperature range: -10°C to +200°C

Function: Normally closed, normally open and double acting normally closed

Normally Closed types:

ASPV10SS-316, ASPV15SS-316, ASPV20SS-316, ASPV25-316, ASPV32-316, ASPV40-316, ASPV50-316, ASPV65-316, ASPV80-316, ASPV100F-316

Normally Open types:

ASPV10SS-316-NO, ASPV15SS-316-NO, ASPV20SS-316-NO, ASPV25-316-NO, ASPV32-316-NO, ASPV40-316-NO, ASPV50-316-NO, ASPV65-316-NO, ASPV80-316-NO, ASPV100F-316-NO

Double Acting Normally Closed types:

ASPV10SS-316-DA, ASPV15SS-316-DA, ASPV20SS-316-DA, ASPV25-316-DA, ASPV32-316-DA, ASPV40-316-DA, ASPV50-316-DA, ASPV65-316-DA, ASPV80-316-DA, ASPV100F-316-DA

Product Variantions:

Product variantions of the above mentioned types are still covered by the listed directives and are CE marked.

EC Declaration of Conformity according to European Directive 2014/68/EU ANNEX II (Module A2)

Audit report 10-07.12372AR, date of certificate 15-01-2025, Expiry 14-01-2026.
(Original certificate checked and verified)

According to the inspection results, the manufacturer is entitled to mark the pressure equipment manufactured within the range of the certificate. The manufacturer may affix the CE Marking to each item of pressure equipment as displayed below.



Signature of authorised person:

Position held: Managing Director