

ROTEX AUTOMATION EUROPE

Address : Bierstraat 117, 3011 XA Rotterdam, The Netherlands

Website : www.rotexautomation.com

E-mail : europe@rotexautomation.com

*Engineering For The Future***DATASHEET**

Type of Valve	: 2/2 Internal Pilot operated diaphragm design Normally Open Valve
Ordering Code	: 24202-12-4R-B12-S0+III-24V-DC-66-NS-H-01
Item Code	:
Port Connection	: 1/2" NPT(F)
Orifice Size (mm)	: 12 mm
Flow Factor (kv)	: 60 LPM
Body Material	: Stainless Steel Cast CF8M (316 Cast) with internal wetted parts of Stainless Steel 316
Manual Override	: Manual Override Not Provided
Seat Seal Material	: NBR
Media	: Air, Clear Water
Main Pressure	: 1 - 20 bar
Media Temp Range	: -25°C to +75°C
Type of Solenoid	: Intrinsically Safe Enclosure with Circuit Ex ia having integrated Terminals, Bottom Cable Entry 1/2" NPT(F), IP67
Size of Coil	: III
Enclosure Material	: Aluminium Cast Powder coated
Voltage	: 24V DC
Power of Coil	: Refer Minimum Operating Parameter
Insulation Class	: Class H
Approval	: IEC Ex + ATEX
Minimum Operating Parameter	: V / I / W - 10V / 20mA / 0.20W
Entity Parameter	: Ui - 32V DC, Ii - 230mA, Pi - 2.3W, Li - 0, Ci - 0
Coil Certificate nr.	: IECEx BAS 12.0128X - Issue 1, Baseefa12ATEX0243X - Issue 1
Marking	: Ex ia IIC T5, Ga (-60 °C ≤ Ta ≤ 75 °C) Ex ia IIC T6, Ga (-60 °C ≤ Ta ≤ 60 °C) Ex ia IIIC T200 125 °C IP67 Da (-60 °C ≤ Ta ≤ 75 °C)

Voltage(V)	10	11	12.5	14	18	22	24	26	30	32
Current(mA)	20	22	25.5	28.5	37	45.5	49.7	54	63	67
Response Time(ms)≤	4800	3800	2500	1600	850	650	450	400	250	250

Response ON Time For Solenoid Valve

Current(mA)	18.5	20	25	30
Open Ckt, Voltage(V)	19.5	19.5	19.5	19.5
Time(ms)≤	5000	4000	2500	2000

Created By: MGFreye **Print Date And Time:** 20/09/2024 21:05

This is System Generated Report