

ROTEX AUTOMATION EUROPE

Address : Bierstraat 117, 3011 XA Rotterdam, The Netherlands

Website : www.rotexautomation.com

E-mail : europe@rotexautomation.com

*Engineering For The Future***DATASHEET**

Type of Valve	: 3/2 Direct acting Normally Closed Valve
Ordering Code	: 30126-1.2-2G-B5-S8+II-24V-DC-39-H-01
Item Code	:
Port Connection	: 1/4" BSP(F)
Orifice Size (mm)	: 1.2 mm
Flow Factor (kv)	: 0.7 LPM
Body Material	: Stainless Steel 316 with internal wetted parts of Stainless Steel 316
Manual Override	: Manual Override Not Provided
Seat Seal Material	: PTFE+VITON
Media	: Air, Clear Water
Main Pressure	: 0 - 63 bar
Media Temp Range	: -40°C to +160°C
Type of Solenoid	: Flameproof Enclosure Ex d having integrated Terminals, Horizontal Cable Entry M20X1.5mm (F)
Size of Coil	: II
Enclosure Material	: Aluminium Cast Epoxy Powder coated
Voltage	: 24V DC (-20%, +20%)
Power of Coil	: 13 W
Insulation Class	: Class H
Approval	: CE - ATEX
Coil Certificate nr.	: ATEX TI22ATEX 278X
Marking	: Ex II 2GD Ex db IIC T6/ T5 Gb Ex tb IIIC T80°C/ T95°C Db, IP66/ IP67 -40 °C < Ta < 60 °C FOR T6 -40 °C < Ta < 70 °C FOR T5

Created By: MGFreye **Print Date And Time:** 12/09/2024 19:42

This is System Generated Report

Rotex Automation Europe is a registered trademark of Rotex Controls B.V.

Rotex Controls B.V. - VAT nr. NL819933259B01

Trade reg : 24443687 Rotterdam

Bankers : ABN Amro : 59.69.83.441 - IBAN : NL34ABNA0596983441 - BIC : ABN ANL 2A.

Phone : + 31 88 505 3 505