

**ROTEX AUTOMATION EUROPE**

Address : Bierstraat 117, 3011 XA Rotterdam, The Netherlands

Website : www.rotexautomation.com

E-mail : europe@rotexautomation.com

*Engineering For The Future***DATASHEET**

<b>Type of Valve</b>	: 3/2 Direct acting Universal Valve
<b>Ordering Code</b>	: 30309-10-4G+II-24V-AC/DC-39-FR-LW20-H-01
<b>Item Code</b>	:
<b>Port Connection</b>	: 1/2" BSP(F)
<b>Orifice Size (mm)</b>	: 10 mm
<b>Flow Factor (kv)</b>	: 30 LPM
<b>Body Material</b>	: Aluminium Hard Anodised
<b>Manual Override</b>	: Manual Override Not Provided
<b>Seat Seal Material</b>	: NBR
<b>Media</b>	: Air
<b>Main Pressure</b>	: 0 - 10 bar
<b>Media Temp Range</b>	: -25°C to +75°C
<b>Type of Solenoid</b>	: Flameproof Enclosure Ex d having integrated Terminals, Horizontal Cable Entry M20X1.5mm (F)
<b>Size of Coil</b>	: II
<b>Enclosure Material</b>	: Aluminium Cast Epoxy Powder coated
<b>Special Version</b>	: Inbuilt Full Rectifier with Surge Suppressor
<b>Voltage</b>	: 24V AC/DC (-10%, +10%)
<b>Power of Coil</b>	: 20 W
<b>Insulation Class</b>	: Class H
<b>Approval</b>	: CE - ATEX
<b>Coil Certificate nr.</b>	: ATEX TI22ATEX 278X
<b>Marking</b>	: Ex II 2GD Ex db IIC T6/ T5 Gb Ex tb IIIC T80°C/ T95°C Db, IP66/ IP67 -40 °C < Ta < 55 C FOR T6 -40 °C < Ta < 70 °C FOR T5

Created By: MGFreye Print Date And Time: 18/09/2024 17:35

This is System Generated Report