

ROTEX AUTOMATION EUROPE

Address : Bierstraat 117, 3011 XA Rotterdam, The Netherlands

Website : www.rotexautomation.com

E-mail : europe@rotexautomation.com

*Engineering For The Future***DATASHEET**

Type of Valve	: 3/2 Direct acting Namur Universal Valve
Ordering Code	: 30318-5-2G-B1+III-230V-AC/DC-39-FR-H-01
Item Code	:
Port Connection	: 1/4" BSP(F)
Orifice Size (mm)	: 5 mm
Flow Factor (kv)	: 8 LPM
Body Material	: Aluminium Hard Anodised, with internal Wetted parts of Stainless Steel 316
Manual Override	: Manual Override Provided Push to operate momentarily, for stayput using Screw Driver push & turn CW to operate valve
Seat Seal Material	: NBR
Media	: Air
Main Pressure	: 0 - 10 bar
Media Temp Range	: -25°C to +75°C
Type of Solenoid	: Flameproof Enclosure Ex d having integrated Terminals, Horizontal Cable Entry M20X1.5mm (F)
Size of Coil	: III
Enclosure Material	: Aluminium Cast Epoxy Powder coated
Special Version	: Inbuilt Full Rectifier with Surge Suppressor
Voltage	: 220V 50Hz/ 60Hz/ DC, 240V 50Hz/ 60Hz/ DC (-20%, +20%)
Power of Coil	: 8 W
Insulation Class	: Class H
Approval	: CE - ATEX
Coil Certificate nr.	: ATEX TI22ATEX 278X
Marking	: Ex II 2GD Ex db IIC T6/ T5 Gb Ex tb IIIC T80°C/ T95°C Db, IP66/ IP67 -40 °C < Ta < 60 °C FOR T6 -40 °C < Ta < 70 °C FOR T5
Created By: MGFreye	Print Date And Time: 18/09/2024 20:33
This is System Generated Report	