


Media: vacuum - acid-detergent-bleach
 Pressure range: 0 to 0.7 bar max
 Media temperature: +5°C to 50°C max
 Ambient temperature: -10° to +40°C
 Media viscosity: 50 centistokes max
 Mounting: any position
 Weight (including coil): 300 g
 Opening or Closing time: 20 mSec Max



2/2 PVC

1/2 DRY- ARMATURE

NORMALLY CLOSED

2 WAY DIRECT ACTING

0 – 0.7 Bar

TYPE C40



PRESSURE

Ø Port BSP	Ø Orifice (mm)	Flow Kv Ltr/Min	Pressure Rating (Bar) ΔP			Seals	Part Number
			Min	Max ~10 w	Max =10W		
1/2	8.0	19	0	0.7	0.4	FKM EPDM	C4012 + seal + voltage
	8.0	19	0	-1	-0.4	FKM EPDM	C4011 + seal + voltage

OPTIONS

IP65 Coil & Connector PG9 – DIN 43650 A
 NPT Thread

ELECTRICAL DATA

Voltage (+10% -5%) Continuous duty 100%	Coil	Power Consumption		Insulation class	Enclosure	Electrical connections
		Inrush	Holding			
~ 24 - 48 - 110 - 230 (50 or 60 Hz)	11630	26VA	14VA	F 155°C	IP 65 with connector	3 spades DIN 43650 DIN 40050 VDE 0110
= 6 - 12 - 24 - 48		10 Watts				

CONSTRUCTION

Body: PVC
 Tube and internal parts: Stainless steel
 Seals and gasket: FKM or EPDM
 Moulded coil: Resin

REPAIR KIT

Coil	11630 or 11630/55 + voltage
Armature	SP + Valve Part Number -ARMATURE
Diaphragm	SP + Valve Part Number - DIAPHRAGM

OVERALL DIMENSIONS

