

SS316 STAINLESS STEEL PUSH-IN FITTING

Specifications

Male straight



NO	4-M5	4-01	4-02	6-M5	6-01	6-02	6-03	8-01	8-02	8-03	8-04	10-02	10-03	10-04	12-02	12-03	12-04
size	4	4	4	6	6	6	6	8	8	8	8	10	10	10	12	12	12
	M5	1/8"	1/4"	M5	1/8"	1/4"	3/8"	1/8"	1/4"	3/8"	1/2"	1/4"	3/8"	1/2"	1/4"	3/8"	1/2"

Male elbow



NO	4-M5	4-01	4-02	6-M5	6-01	6-02	6-03	8-01	8-02	8-03	8-04	10-02	10-03	10-04	12-02	12-03	12-04
size	4	4	4	6	6	6	6	8	8	8	8	10	10	10	12	12	12
	M5	1/8"	1/4"	M5	1/8"	1/4"	3/8"	1/8"	1/4"	3/8"	1/2"	1/4"	3/8"	1/2"	1/4"	3/8"	1/2"

Male branch tee



NO	4-M5	4-01	4-02	6-M5	6-01	6-02	6-03	8-01	8-02	8-03	8-04	10-02	10-03	10-04	12-02	12-03	12-04
size	4	4	4	6	6	6	6	8	8	8	8	10	10	10	12	12	12
	M5	1/8"	1/4"	M5	1/8"	1/4"	3/8"	1/8"	1/4"	3/8"	1/2"	1/4"	3/8"	1/2"	1/4"	3/8"	1/2"

Male run tee



NO	4-01	4-02	6-01	6-02	8-01	8-02	10-02	10-03	12-02	12-03	12-04						
size	4	4	6	6	8	8	10	10	12	12	12						
	1/8"	1/4"	1/8"	1/4"	1/8"	1/4"	1/4"	3/8"	1/4"	3/8"	1/2"						

Bulkhead female union



NO	4-01	4-02	6-01	6-02	6-03	8-01	8-02	8-03	10-02	10-03	10-04	12-02	12-03	12-04			
size	4	4	6	6	6	8	8	8	10	10	10	12	12	12			
	1/8"	1/4"	1/8"	1/4"	3/8"	1/8"	1/4"	3/8"	1/4"	3/8"	1/2"	1/4"	3/8"	1/2"			

Female straight



NO	4-01	4-02	6-01	6-02	6-03	8-01	8-02	8-03	10-02	10-03	10-04	12-02	12-03	12-04			
size	4	4	6	6	6	8	8	8	10	10	10	12	12	12			
	1/8"	1/4"	1/8"	1/4"	3/8"	1/8"	1/4"	3/8"	1/4"	3/8"	1/2"	1/4"	3/8"	1/2"			

Union straight



NO	4	6	8	10	12
size	4	6	8	10	12

Union tee



NO	4	6	8	10	12
size	4	6	8	10	12

Bulkhead union



NO	4	6	8	10	12
size	4	6	8	10	12

Specifications

Model	S6 series
Fluid	Air
Operating pressure range	0~8 kgf/cm ²
Ambient temperature	0°C ~ 180°C