


Media: air – water – light oil  
 Pressure range: 2 to 300 Bar max  
 Media temperature: 150°C max  
 Ambient temperature: -10° to +60°C  
 Media viscosity: 40 centistokes max  
 Mounting: vertical position, coil up  
 Weight (including coil): 5000 g  
 Opening or Closing Time: 200mSec Max



NC

# 2/2 Stainless

## 1"

### NORMALLY CLOSED

### 2 WAY SERVO ASSISTED

### 2 – 300 Bar

## TYPE 215256 - 259



#### PRESSURE AIR + GAS

Ø Port BSP	Ø Orifice (mm)	Flow Kv Ltr/Min	Pressure Rating (bar) ΔP		Seals	Max Media Temp °C	Part Number
			Min	Max			
1	15	70	2	200	PTFE + FKM	150	215256 + 821001 + voltage
	15	70	10	300	VOLTALEF + FKM	150	215258 + 971001 + voltage

#### PRESSURE OIL + LIQUID

1	15	70	2	200	PTFE + FKM	150	215257 + 821001 + voltage
	15	70	10	300	VOLTALEF + FKM	150	215259 + 971001 + voltage

#### OPTIONS

IP65 Coil & Connector PG9 – DIN 43650 A

Explosion proof enclosure: Protection II G/D EExdIICT6 ATEX  T6 Ambient -10°C to +40°C or T4 -10°C to +60°C

Other custom made options: ATEX EExmIIT4: Manual Over Ride: Normally Open Function: NPT Thread

Included  
POR  
POR

#### ELECTRICAL DATA

Voltage (-10% + 15%) Continuous duty 100%		Coil	Power Consumption		Insulation class	Enclosure	Electrical connections
~	=		Inrush	Holding			
24 - 48 - 110 - 230 (50 or 60 Hz)		31037	48 VA	24 VA	F 155°C	IP 65 with connector	3 spades DIN 43650A DIN 40050 VDE 0110
	12 - 24 - 48 (DC)		13.7 Watt				

#### CONSTRUCTION

Body: AISI 316L Stainless steel

Tube and internal parts: Stainless steel

Seals and gaskets: PTFE + FKM or VOLTALEF + FKM

Moulded coil: Resin

#### REPAIR KIT

Coil	31037 + voltage
Complete plunger + O' rings + complete piston	KIT + valve part number

#### OVERALL DIMENSIONS

