


Media: air - gas
 Inlet Pressure: 60 Bar max
 Outlet Pressure: 0.5 to 30 Bar
 Media temp: -10°C to +70°C
 Ambient temp: -10°C to +70°C
 Mounting: upright (USR any)



Stainless F R L

1/4 – 1/2

316 Stainless Steel

Manual, Semi, Fully Auto Drain

0.5 – 60 Bar

TYPE USFRL02-03-04



PRESSURE

Ø Port BSP	Max Flow Air L/min @ 6Bar (ANR)	Kg	Max Inlet Pressure (Bar)	Working Pressure (Bar)		Combination	Part Number
				Min	Max		
1/4(02)	2080,2200,2500	3.8	60	0.5	12	F/R+L	USFR/LB + port
			60	12	30		USFR/L + port
3/8(03)	2200,2500,3800	2	60	0.5	12	Filter/Regulator	USFRB + port
			60	12	30		USFR + port
1/2(04)	2440,2450,3030	1.65	60	0.5	60	Filter	USF + port
	1950,2250,2520		60	0.5	12	Regulator	USRB + port
	2500,2525,4100	1.4	60	12	30		USR + port
		1.75	60	0.5	60	Lubricator	USL + port

OPTIONS

5 Micron SUS316 Filter Element (USFRL, USFR + USF)
 Semi-Automatic - drain below 0.5 bar (USFRL, USFR, USF)
 Pressure Gauge, Blanking Plug, Mounting Bracket and Screws (USFRL, USFR, USR)
 40 Micron SUS316 Filter Element (C) (USFRL, USFR, USF)
 Fully Automatic Drain (D) (USFRLB, USFRB, USFB) 10 Bar Max (D0014W)
 Manual Drain (H)

Included
 Included
 Included

CONSTRUCTION

Body, Regulator, Filter (110cc) Lubricator (130cc) Bowl, Filter Elements, Mounting Bracket, Blanking Plug: 316 Stainless Steel
 Pressure gauge: cover 304 Stainless Steel / Thread 316 Stainless Steel
 O rings: Viton
 Test Pressure: 60 Bar

OVERALL DIMENSIONS

