



Media: air
 Pressure range: 0 to 8 Bar
 External pilot: 1.5 to 7 Bar
 Media temperature: +80°C max
 Ambient temp: -10°C to +80°C max
 Mounting: any position
 Weight : (See dimensions)



5/2 5/3 Pneumatic Valve

1/8, 1/4, 3/8 & 1/2 BSP Width 26/30/34mm
 5/2 S/RETURN or 5/2 & 5/3 D/ACTING
 0 – 8 Bar
TYPE SK520/530



5/2 Way Single Acting SK520S Series

Ø Port BSP	Ø Orifice (mm ²)	Pressure Rating (Bar) ΔP		Max Working	Part Number	Width (mm)	
		Min	Max				
1/8	18	0	8	10	SK52001S	26	
1/4	18	0	8	10	SK52002S		
3/8	35	0	8	10	SK52003S	30	
1/2	70	0	8	10	SK52004S	34	

5/2 Way Double Acting SK520D Series

1/8	18	0	8	10	SK52001D	26	
1/4	18	0	8	10	SK52002D		
3/8	35	0	8	10	SK52003D	30	
1/2	70	0	8	10	SK52004D	34	

5/3 Way Double Acting SK530D Series

1/8	14	0	7	10	SK53001D	26	
1/4	14	0	7	10	SK53002D		
3/8	32	0	7	10	SK53003D	30	
1/2	54	0	7	10	SK53004D	34	

OPTIONS

NPT Thread
 5/3 way exhaust centre (SK530X), or 5/3 way pressure centre (SK530Y)

CONSTRUCTION

Body: Anodised Aluminium, Tube and internal parts: Stainless steel, Seals and gaskets: NBR

OVERALL DIMENSIONS

