

Ambient temperature -40°C to +60°C
 Adjustable interval and discharge times
 Mounting: Any position
 CE Tested
 Weight 80g
 Fully Automatic - no maintenance
 Simple to install
 SVT22 fit all DIN43650A coils
 SVT11 fit all DIN 43650B coils

Solenoid Valve Timer

SOLID STATE

24 - 240v AC or DC

DIN43650A + DIN43650B

Type SVT22 + SVT11



Models

Cyclic Repeat Solenoid Valve Timers	Front View	Rear View	Power On Cycle adjustment	Power Off Cycle adjustment	Part Number
<p>DIN 43650A Upon application of power the timer resets, enters the ON state for a period of T1, then switches OFF for a period T2. This cycle repeats until power is removed.</p>			0.5 - 10 Sec	0.5 - 45 Min	SVT22
			0.5 - 10 Sec	25 - 150 Min	SVT22N-02
			20- 300mSec	0.5 - 60 Min	SVT22N-03
			0.5 - 60 Min	0.5 - 10 Sec	SVT22N-04
			0.3 - 5 Min	0.1 - 60 Min	SVT22N-05
			0.5 - 10 Min	0.5 - 60 Min	SVT22N-06
			0.5 - 10 Sec	0.5 - 10 Sec	SVT22N-07
			0 - 20 Min	0 - 20 Min	SVT22N-08
			0.5 - 60 Sec	0.5 - 45 Min	SVT22N-09
			0.3 - 30 Sec	0.5 - 45 Min	SVT22N-10
			0.5 - 10 Sec	0.5-12Hrs	SVT22N-12
			<p>Fully Programmable ON then Off or OFF then ON 1 Second to 59 Hrs 59 Min 59 Sec AC/DC 7-36 volt or 110-240 volt DIN43650A</p>		
<p>Fully Programmable ON then Off, OFF then ON or Single Shot 1 Second to 99 Hrs 59 Min 59 Sec AC/DC 7-36 volt or 110-240 volt DIN43650A</p>	<p>On Off</p>		1 Sec to 100 Hrs	1 Sec to 100 Hours	SVTD-DIGITAL
			Single Shot		
<p>DIN 43650B Output DIN43650A Input</p> <p>Upon application of power the timer resets enters the ON state for a period of T1, then switches OFF for a period T2. This cycle repeats until power is removed.</p>			0.5 - 10 Sec	0.5 - 45 Min	SVT11

OPTIONS

Manual test switch - LED Power ON light - LED Power OFF light
 Single shot timer: Application of power the timer resets, enters the ON state for a period T1, then switches OFF indefinitely
 Delay Timer: Application of power the timer resets, enters the OFF state for a period T2, then switches ON indefinitely
 Delayed repeat Cycle: Power timer resets and OFF state for period T2, then ON for a period T1. This sequence repeats until power is removed
 Single Cycle Timer: Power ON timer enters OFF for a period T2, then switches ON for period T1. Then switches OFF & remains OFF indefinitely
 12vDC - 440vAC - 10 Amp version - Limitless time scale availability - Horizontal - Various Colours and other custom options available

ELECTRICAL DATA

Voltage (24 - 240v AC or DC) Continuous duty 100%	Power Consumption	Power Connection	Enclosure	Electrical connections
~ 24 to 240 50/60 Hz	4 mA Max	1 Amp Max	IP 65 with connector	DIN 43650 DIN 40050 VDE 0110
= 24 to 240 vDC				

CONSTRUCTION

Housing material ABS plastic FR Grade

OVERALL DIMENSIONS

