

**ROTEX AUTOMATION EUROPE**

Address : Bierstraat 117, 3011 XA Rotterdam, The Netherlands

Website : www.rotexautomation.com

E-mail : europe@rotexautomation.com

*Engineering For The Future***DATASHEET**

<b>Type of Valve</b>	: 3/2 Direct acting Low Power (<5W) Universal Valve
<b>Ordering Code</b>	: P3017V01-R-5-2G-B5+IV-24V-DC-62-MS-H-01
<b>Item Code</b>	:
<b>Port Connection</b>	: 1/4" BSP(F)
<b>Orifice Size (mm)</b>	: 5 mm
<b>Flow Factor (kv)</b>	: 8 LPM
<b>Body Material</b>	: Stainless Steel 316 with internal wetted parts of Stainless Steel 316
<b>Manual Override</b>	: Manual Override Not Provided
<b>Seat Seal Material</b>	: NBR
<b>Media</b>	: Air, Clear Water
<b>Main Pressure</b>	: 0 - 10 bar
<b>Media Temp Range</b>	: -25°C to +75°C
<b>Type of Solenoid</b>	: Intrinsically Safe Coil with Circuit having integrated Terminals, Bottom Cable Entry M20X1.5mm(F), IP67
<b>Size of Coil</b>	: IV
<b>Enclosure Material</b>	: Aluminium Cast Powder coated
<b>Voltage</b>	: 24V DC
<b>Power of Coil</b>	: Refer Minimum Operating Parameter
<b>Insulation Class</b>	: Class H
<b>Approval</b>	: IEC Ex + ATEX
<b>Minimum Operating Parameter</b>	: V / I / W - 12.5V / 25.5mA / 0.3W
<b>Entity Parameter</b>	: Ui - 32V DC, Ii - 230mA, Pi - 2.3W, Li - 0, Ci - 0
<b>Coil Certificate nr.</b>	: IECEx BAS 12.0128X - Issue 1, Baseefa12ATEX0243X - Issue 1
<b>Marking</b>	: Ex ia IIC T5, Ga (-60 °C ≤ Ta ≤ 75 °C) Ex ia IIC T6, Ga (-60 °C ≤ Ta ≤ 60 °C) Ex ia IIIC T200 125 °C IP67 Da (-60 °C ≤ Ta ≤ 75 °C)

<b>Voltage(V)</b>	12.5	14	18	22	24	26	30	32
<b>Current(mA)</b>	25.5	28.5	37	45	49.7	54	63	67
<b>Response Time(ms)≤</b>	2500	1600	850	650	450	400	250	250

**Response ON Time For Solenoid Valve**

<b>Current(mA)</b>	18.5	20	25	30
<b>Open Ckt, Voltage(V)</b>	19.5	19.5	19.5	19.5
<b>Time(ms)≤</b>	5000	4000	2500	2000

**Created By:** MGFreye      **Print Date And Time:** 17/09/2024 14:33

This is System Generated Report