


# Stainless Steel Miniature Filter



II 2G Ex h IIC T4 Gb  
 II 2D Ex h IIC T135°C Db  
 -10 °C ≤ Ta ≤ 70 °C

## Symbol



## Features

1. For high pressure use, corrosion and chemical resistance.
2. Good performance in chemically working environments and outdoor facility.
3. Suitable for semi-conductor industry.
4. Effectively removes water and particle.
5. Strict quality control.
6. Light weight, compact size for space saving.
7. CE and EX-proof certified.



## How to order

SSF200	—	02	N	C	H
Stainless Steel SUS316 Miniature Filter		Port size	Thread	Filtration	Drain
		02 : 1/4"	Blank : G N : NPT R : Rc	Blank : 5µm C : 40µm	Blank : Semi-auto drain H : Manual drain

## Specifications

Model	SSF200
Port size	1/4"
Fluid	Compressed air
Body material	Stainless steel SUS316
Bowl material	Stainless steel SUS316
Filter element material	Stainless steel SUS316
Filtration	5µm (Standard), 40µm (Option)
Operating pressure range	0.5 ~ 30 kgf/cm <sup>2</sup>
Max. inlet pressure	30 kgf/cm <sup>2</sup>
Max. flow rate l/min 40µm	1900
Ambient temperature	-10°C ~ 70°C
Filter bowl capacity	105cc
Proof pressure	40 kgf/cm <sup>2</sup>
Standard drain	Semi-auto drain (Drains below 0.5kgf/cm <sup>2</sup> )
Net weight	1260g
Accessories	Mounting bracket, Plug

## Dimensions

