


Media: air - gas
 Inlet Pressure: 60 Bar max
 Outlet Pressure: 0.5 – 28 Bar
 Media temp: -10°C to +70°C
 Ambient temp: -10°C to +70°C
 Mounting: Upright (USR any)
 Weight: 3.36-10.34Kg



Stainless F R L

3/4 – 1

316 Stainless Steel

Manual, Semi or Auto Drain

0.5 - 60 Bar

TYPE USFR/L06-08



PRESSURE

Ø Port BSP	Max Flow Air L/min @ 6Bar (ANR)	Kg	Max Inlet Pressure (Bar)	Working Pressure (Bar)		Combination	Part Number
				Min	Max Outlet		
3/4(06) 1(08)	7600,8000	10.34	60	0.5	12	F+R+L	USF+R+LB + port
	15200				28		USF+R+L + port
	7600,8000	7.96			12	F/R + L	USF/R+LB + port
	15200				28		USF/R+L + port
	8700	4.58			12	F/R	USF/RB + port
	9100				28		USF/R + port
	9600	3.95		12	Filter	USFB + port	
	19200			60		USF + port	
	9000,9400	3.4		0	12	Regulator	USRB + port
	18000,22000				28		USR + port
	13200	3.36			12	Lubricator	USLB + port
	26400				60		USL + port

OPTIONS

5 Micron Filter Element, Semi auto Drain, Pressure Gauge, Mounting Brackets + screws (USFRL, USF/R, USF)
 40 Micron Filter Element (C) (USFRLB, USF/R+LB, USFRB, USFB)
 Manual drain (H) (USFRLB, USF/R+LB, USFRB, USFB)
 Fully automatic drain (D) (USFRLB, USF/R+LB, USFRB, USFB) 10 Bar Max (D0014W)
 Bowl Viewer (W) (USFRLB, USF/R+LB, USFRB, USFB, USLB 12 Bar Max)
 NPT Thread or non-relieving regulator

Included

CONSTRUCTION

Body, Regulator, Filter (200cc), Lubricator Bowl (220cc), Mounting Bracket, Blanking Plug, Filter Element: 316 Stainless Steel
 Pressure gauge: Case 304 Stainless Steel / Thread 316 Stainless Steel
 O rings: Viton
 Test Pressure: USFRL 80 Bar USFRLB 40 Bar, Sensitivity 5% F.S.
 External finish to 0.8 Ra (Except T handle, bar, screw + nut)

OVERALL DIMENSIONS

